INSTALLATION MANUAL
FOR

Cadillac - CTS - 2003-2007

Cadillac -CTS-V - 2004-2007

Mount Location: Right of heater control

MVM
Multi Vehicle Mount

MVM-35-05
Includes PHS-203 Ultra Slim Swivel

Thank you for purchasing your new Bracketron **MVM** Multi Vehicle Mount.

The Multi Vehicle Mount is an (end user-installer) modifiable professional mounting bracket for most all mobile electronics requiring a steady and secure installation in a motor vehicle. The MVM installs behind your vehicles dash panel using existing or non-visible holes and is designed to cleanly protrude out from your vehicle's dash panel.

Before installing, you must take the time to read and understand this installation manual and read all the warnings accompanying this product.

Instructions Include: tools needed for install, directions for dash panel removal, directions for modifying the MVM if required.

You can download this manual and any updates from
http://www.bracketron.com/downloads

IMPORTANT INFORMATION

IMPORTANT INFORMATION

Please read instructions completely before installing this Bracketron MVM Mount. All instructions are written from the drivers seat vantage point looking forward at the vehicles dash. We advise caution whenever you are removing or handling plastic parts of a vehicles dash. **WARNING:** Unnecessary force or pressure can cause pieces to crack or break.

PARTS INCLUDED: MVM-35-05 Mount, 3 - #8x3/4" Self Tapping Screws PHS-203 Ultra Slim Swivel and Hardware.

TOOLS NEEDED FOR DASH PANEL DISASSEMBLY

Dash Trim Tool (Part #SIT-104)
2 Phillips Screwdriver
7mm nut driver
Fiskars 8511 Craft Hand Drill (recommended)
5/64" Drill Bit
9/32" Open End Wrench (for swivel)
Marking Pen

TOOLS NEEDED FOR MVM MODIFICATION (*if required*)

4 inch Mounted Bench Vise
12 oz. Ball Pein Hammer
Standard Tin Snips
Small File

Note: The hole pattern on the face of the MVM maybe different then what is shown in the pictures.

DASH DISASSEMBLY INSTRUCTION

1. Remove the coin tray/ash tray and remove the 7mm screw through the hole beneath the ash tray.

2. With a dash trim removal tool, carefully pry out on the heather control trim and remove it.

3. Skip to the next page to modify your MVM if you have not done so already.

4. With a razor blade, carefully trim the plastic ridge on the right side of the dash. With the supplied phillips screw, attach the MVM to the inside of the dash as shown.

5. Carefully reinstall the dash in reverse order securing all screws and clips to the bezel. Install the included Ultra Slim Swivel #PHS-203 to your Multi Vehicle Mount or any other AMPs compatible device.

   Your installation is complete

MVM MODIFICATION INSTRUCTIONS

PLEASE NOTE

The Bracketron MVM-35-05 mount is a modifiable mounting bracket. The illustrations on the left show how this mount should look during and after the modification steps in order to fit the listed vehicles on the front page of this manual. Many vehicle applications may not require any modifications to the mount. If this is the case it will be noted below and there will be no steps to follow on this page.

Picture 1

Picture 2

Picture 3

Note: The hole pattern on the face of the MVM maybe different then what is shown in the pictures.

5. Position the MVM as shown in PICTURE 1.

6. Cut the MVM on the RED LINES in PICTURE 2 and bend on the YELLOW LINES in relation to the final product in Picture 3.

7. Return to Step 4 to complete your installation.

Note: Please see page 3 in this manual for PHS-203 Ultra Slim Swivel Instructions.

© Bracketron Inc, 2007 All rights reserved.
The information in this document is subject to change without notice. Bracketron Inc. assumes no responsibility for any errors that may appear in this document nor do we assume any liability in connection with its use. This supersedes and voids all previous literature. Please contact the sales department for additional information. Bracketron Inc. will not be responsible or liable for damage to vehicles in the installation and or removal of this Bracketron Inc. mount. Bracketron Inc. will not be liable for personal injuries or damage to property resulting from a motor vehicle accident and or improper installation of this Bracketron Inc. mount.

Bracketron Inc 5249 West 73rd Street, Suite G, Edina, MN 55439
tel: 952-746-7775 fax: 1-800-660-1784 toll free: 1-866-237-4443
email: sales@bracketron.com web: www.bracketron.com

PHS-203 ULTRA SLIM SWIVEL INSTRUCTIONS

PLEASE READ INSTRUCTIONS COMPLETELY BEFORE INSTALLING THIS BRACKETRON MOBILE SOLUTION.

This Professional Swivel Mount Solution is designed to be mounted to your MVM or any other 4 hole AMPs compatible mounting device. The Ultra Slim Swivel is compact with a low profile and is designed to provide adjustability to devices such as Satellite Radio Receivers, GPS monitors or Mobile Phones. The Ultra Slim Swivel angles your device for better viewing, tilting approx 15° in all directions and swivels 360° degrees for maximum adjustability. All mounting hardware is included in the kit along with our AMPs adapter plate to attach devices that support T- Notch mounting.

PARTS INCLUDED

1 - Ultra Slim Swivel
1 - AMPs Adapter Plate
4 - M4 x 10 Hex Head Screws
4 - M4 x 10 Pan Head Screws
4 - M4 x 12 Pan Head Screws
4 - M4 Hex Head Nuts
4 - M4 Nylon Locking Nuts
4 - M4 Star Washers

1 **Note: The swivel can be installed before or after the mount is installed in the vehicle.** Attach the Ultra Slim Swivel to any MVM or CBM Mount or other AMPs mounting device by inserting the M4x10 Pan Head screws through the holes on the back half of the swivel. Align the screws up with the holes on the mount. Attach the M4 Nylon Locking Nuts only finger tight. Rotate the front half of the swivel to gain access to the M4x10 Pan Head screws. (See Picture 1&2) Tighten all 4 screws with a #2 Phillips screwdriver and 9/32″ open end wrench.

Picture 1

Picture 2

Picture 3



2 Tighten the center screw to adjust the desired tension of the swivel. (See Picture 3) **Note:** If Swivel becomes loose over time, you can grasp the swivel and pull toward you lightly while rotating it clockwise. This will tighten the swivel allowing you to create the desired tension needed.

3

For T- Notch Devices

Attach the AMPs T- Notch Adapter to the front half of the swivel using the M4x12 Pan Head screws. Attach the M4 Star Washers and M4 Hex Nuts to the screws and tighten the plate down with the #2 screwdriver and 9/32″ open end wrench. Slide your device onto the T- notch Adapter plate to secure it to the swivel. (See Pictures 4)

For AMPs Devices with Inserts

Attach your AMPs device using the M4x10 Hex Head screws and M4 Star Washers. Align the holes on the device with the holes on the front half of the swivel. Slide the Star Washers onto the Hex Head screws. Insert the screws through the swivel and into your device only finger tight. Tighten down the device with the 9/32″ open end wrench. Your device is now secure to the swivel. (See Pictures 5)

Picture 4

Picture 5

© Bracketron Inc, 2007 All rights reserved.
The information in this document is subject to change without notice. Bracketron Inc. assumes no responsibility for any errors that may appear in this document nor do we assume any liability in connection with its use. This supersedes and voids all previous literature. Please contact the sales department for additional information. Bracketron Inc will not be responsible or liable for damage to vehicles in the installation and or removal of this Bracketron Inc mount. Bracketron Inc will not be liable for personal injuries or damage to property resulting from a motor vehicle accident and or improper installation of this Bracketron Inc mount.

Bracketron Inc 5249 West 73rd Street, Suite G, Edina, MN 55439
tel: 952-746-7775 fax: 1-800-660-1784 toll free: 1-866-237-4443
email: sales@bracketron.com web: www.bracketron.com